

TL-181 1-Channel Indoor Data Logger

TL-182 5-Channels Indoor Data Logger



LOGGER FEATURES

- 5 Channels (1 internal, 4 external)
- Real-time Excel output
- 4 external sensor types:
 1. Temperature
 2. Humidity
 3. AC current
 4. 4-20 milliamps
 5. 0 to 3.3 Volts DC
 6. Frequency input (0 to 1000 Hz)
 7. Pulse width input
- Blinking LED light confirms operation
- 1 year user-replaceable battery
- Battery level indication at launch
- RS-232 communication port

LOGGER SPECIFICATIONS

- 5 channels - (1 channel for the internal temperature sensor and 4 channels inputs for measurements of temperature, resistance or switch status)
- Clock accuracy: + -1 minute per month.
- 128K bytes of EEPROM stored data - retains data even if battery fails

SOFTWARE FEATURES

- Real-time Excel output
- Full-feature program to download, analyze and real-time display logger information.
- Sampling rate: 4/second to 1 time per year sampling rate.
- Programmable start time/date
- EEPROM memory
- Battery check at launch

ACCESSORIES

- Wall mounting bracket

POWER SUPPLY

- Battery type: 9V
- Battery life: 1 year

OPERATION CONDITION

- Operating temperature: -40 to 70°C (-222 to 158°F)
- Operating humidity: 0 to 95% relative humidity.
- Storage temperature & humidity: Same as above.

DIMENSION

- Size: 97 x 62 x 27mm (L x W x H)
- Weight: About 100g (including battery)

